Guardian® RHP143LSplit System Heat Pump 14.3 SEER2/7.5 HSPF2 | 1.5 to 5 Tons



The Guardian® RHP143L Heat Pumps provide the next grade of efficiency in an entry-level model with its 14.3 SEER2 cooling efficiency and high EER2 performance required in southern US climates. Expertly designed and engineered, and rigorously tested, these RHP143L Heat Pumps offer the

Designed and constructed for optimal installation, performance and serviceability

latest in energy savings and lasting performance for years to come.

- Meets new updated DOE 2023 minimum standards
- Durable powder-coating painted finish
- Low-sound fan design
- Easy installation and serviceability

Heat pumps and air conditioners

A heat pump (HP) is a high-performance air conditioner (AC) that also provides heat by using a valve to reverse the refrigeration cycle. Unlike typical AC units, heat pumps leverage the heat produced through the refrigeration cycle to heat the home. This can help offset the reliance on natural gas for heat and save money.

14.3 SEER2 can save you up to 40% on energy bills*





^{*} The percentage savings are calculated based on the \$0.14/kWh national average for three-ton 8 SEER versus 14.3 SEER2 units.

Quality design and construction

- NEW two-stage performance on 2-5 Ton models
- Designed for optimal performance in southeastern and southwestern US regions (meets DOE 2023 minimum requirements)
- · Tube-in-fin coils for maximum efficiency and durability
- Extruded louver for extra strength
- Automotive-grade powder-coating painted finish with industry-leading 1,000-hour salt-spray rating
- Unique low-sound fan design
- Eco-friendly: CFC-free R-410A refrigerant delivers environmentally friendly performance with zero ozone depletion

Industry's most serviceable unit

- Streamlined footprint for easier transportation and installation
- Removeable fan guard
- Swing-out control box
- Full access from the top and side



sku	Tonnage	Voltage	Liquid Line (inches)	Suction Line (inches)	Dimensions (inches)			Sound (dBA)	Approximate Operating Weight
					Н	w	D	(35%)	(lbs.)
RHP143L18B21S	1.5	208-230V	3/8	3/4	33 1/4	24	24	73	150
RHP143L24B21S	2.0	208-230V	3/8	3/4	36 1/4	24	24	73	150
RHP143L30B21S	2.5	208-230V	3/8	3/4	30	29 1/4	29 1/4	73	165
RHP143L36B21S	3.0	208-230V	3/8	3/4	33 1/4	35 1/4	31 3/4	73	185
RHP143L42B21S	3.5	208-230V	3/8	7/8	39 1/2	35 1/4	31 3/4	73	215
RHP143L48B21S	4.0	208-230V	3/8	7/8	39 1/2	35 1/4	31 3/4	76	210
RHP143L60B21S	5.0	208-230V	3/8	1 1/8	46	38	34 1/4	76	230



Lower cost of ownership

14.3 SEER2 cooling efficiency can save energy costs compared to older units, and quality engineering reduces repairs to save you money.



Confidence guaranteed

Industry-leading warranties ensure years of dependability.



Quiet operation

Direct-drive fan design minimizes vibration and sound.



Trusted quality

Manufacturer-backed warranty: our industry-best warranty protection provides peace of mind.





To receive the extended 10-Year Parts Limited Warranty or premium system warranty for qualifying units, you must register online at www.upgproductregistration.com. Registration must be completed within 90 days of installation or 90 days of the closing date for new home construction. Failure to register online within 90 days results in a standard 5-Year Parts Limited Warranty. Failure to return the registration card does not affect rights under the standard warranty.

Replacing a full system? Pair with a Guardian JHET Single-Piece or JMET Modular Air Handler Unit or furnace for optimal performance.



